

# MEASURES, RULES, SQUARES & LEVELS

## HEAVY-DUTY ELEVATING TRIPODS

- Lightweight durable aluminum construction with elevating platform
- 5/8"-11 mounting screw
- Sharp pointed feet for uneven terrain
- Retractable rubber covers for slick surfaces
- Folds for easy portability
- Adjustable height ranges from 49.825" to 118.25" (126.5 cm to 300 cm)

**Model No. TGZ564**  
**Mfg. No. 40-6330**  
**Price/Each \$**



## ALUMINUM TRIPODS

- Lightweight durable aluminum construction
- 5/8"-11 mounting screw
- Sharp pointed feet for uneven terrain
- Retractable rubber covers for slick surfaces
- Folds for easy portability
- Adjustable height ranges from 41.75" to 67" (106 cm to 170 cm)

**Model No. TGZ570**  
**Mfg. No. 40-6340**  
**Price/Each \$**



## MAGNETIC TORPEDO LASER LEVELS, FLAT BOTTOM

- Built-in, rotating head changes from point to horizontal or vertical lines
- Cross-check vial for more accurate levelling
- Machined gauging edge
- Includes: Laser level, two AAA batteries and carrying case



### TECHNICAL SPECIFICATIONS

**Model No. TGZ561**  
**Mfg. No. 40-6164**  
**Laser wave length:** 650 nm  $\pm$  10 nm  
**Laser classification:** Class 111a  
**Accuracy:**  $\pm$  1/8" @ 50' ( $\pm$  1 mm @ 5 m)  
**Working range:** Max. 100' (30 m) depending on light conditions  
**Working temperature:** 14°F to 113°F (-10°C to 40°C)  
**Price/Each \$**

## MAGNETIC TORPEDO LASER LEVELS, V-GROOVED BOTTOM

- Built-in, rotating head changes from point to horizontal or vertical lines
- Cross-check vial for more accurate levelling
- V-grooved bottom for use on pipes or conduit
- Includes: Laser level, two AAA batteries, levelling bracket, two mounting straps and carrying case



### TECHNICAL SPECIFICATIONS

**Model No. TGZ562**  
**Mfg. No. 40-6174**  
**Laser wave length:** 650 nm  $\pm$  10 nm  
**Laser classification:** Class 111A  
**Accuracy:**  $\pm$  1/8" @ 50' ( $\pm$  1 mm @ 5 m)  
**Working range:** Max. 100' (30 m) depending on light conditions  
**Working temperature:** 14°F to 113°F (-10°C to 40°C)  
**Price/Each \$**

## TORPEDO LASER SPIRIT LEVEL

- Practical use as a laser level or as a normal spirit level
- The flexible wall holder for all surfaces enables convenient working
- Integrated point laser that precisely transfers heights in the room
- Soft grip for better and more comfortable hold
- Horizontal, vertical or diagonal laser lines, as well as point laser
- High quality, bright laser for particularly clearly visible laser lines and laser points
- Working range up to 3 meters (laser line) and 20 meters (laser point)

**JOHNSON**



### TECHNICAL SPECIFICATIONS

**Model No. TYO566**  
**Mfg. No. 40-6188**  
**Laser classification:** Class 2  
**Laser line wave length:** 635 Nm  
**Laser point wave length:** 650 Nm  
**Laser line width:** 100 LUX, 3 mm/3 m  
**Laser point dia.** 100 LUX, 15 mm/20 m  
**Laser line accuracy:** 1 mm/m  
**Laser point accuracy:** 0.5 mm/m  
**Level accuracy:** 1 mm/m  
**Max. working range:** 65' (20 m)  
**Working temperature:** 0-40°C  
**Working time:** >15 h  
**Power:** 3 V, 2-AAA Battery  
**Overall length:** 8"  
**Price/Each \$**

## 2-AXIS/3-BEAM LASER POINTERS

- Self-levelling plumb bob is accurate to  $\pm$ 1/4" @ 100'
- One button operation is fast and easy to use
- Overmolded housing helps maintain calibration under job site conditions
- Focused laser beam keeps dot small even over long distances for improved accuracy and visibility
- Locating magnets hold laser plumb bob to metal track for easy positioning
- Cross-hair beam pattern helps user find centre of beam
- Includes: Kit box

**DEWALT**



### TECHNICAL SPECIFICATIONS

**Model No. TSW589**  
**Mfg. No. DW083K**  
**Power supply:** 4 AA Alkaline  
**Indoor visibility range:** +/- 100'  
**Laser classification:** Class II (<1.5 mW) @ 635 nm  
**Price/Each \$**

## SELF-LEVELLING LINE LASERS (HORIZONTAL & VERTICAL)

- Accurate to +/- 1/8" @ 30' for level applications
- Built-in magnetic pivot bracket mounts easily on metal surfaces
- Overmolded housing for job site durability
- One button operation and control panel for ease of use
- Includes: 3 AA batteries for 20+ hours run-time and kit box

**DEWALT**



### TECHNICAL SPECIFICATIONS

**Model No. TLZ506**  
**Mfg. No. DW088K**  
**Power supply:** 3 AA batteries  
**Self-Levelling Range:** 5°  
**Indoor visibility range:** 100'  
**Laser classification:** Class II  
**Price/Each \$**